



## **2016 KRONE AZ 18F KOFFER MIT HB**

**CHF 7'000**

AZ 18F Koffer mit HB , 08/07/2016

**Guxim Berisha**

Verkauf Jestetten


T: +49 151 463 16600

M: +49 151 463 16600

M: g.berisha@trucktrade.com

[WhatsApp](#)

[Standort](#)



---

**SKU:** 24612T

**Kategorien:** [Koffer](#), [LKW-Anhänger](#)

## **BESCHREIBUNG**

### **HAUPTMERKMALE / AZ 18F KOFFER MIT HB**

---

Interne Referenz	24612T
Fahrzeugmodell	AZ 18F Koffer mit HB
Produktkategorie	LKW-Anhänger, Koffer
Fahrgestellnummer	WKE AZ0 000 006 614 26
Stammnummer	426.735.880
Inverkehrssetzung	08/07/2016

letzte MFK oder TÜV	27/07/2023
Allgemeiner Fahrzeugzustand	sehr gut
Aufhängung	Luft-Luft

### FAHRERHAUS

---

Anzahl Sitze	2
Fahrzeugausstattung	ABS, ESP

### ACHSEN & BEREIFUNG

---

Anzahl Achsen	2
Achse 1	385 / 55 R 22.5 / 5mm , Luftfederung
Achse 2	385 / 55 R 22.5 / 6mm, Luftfederung

### GEWICHTE & MASSE

---

Gesamtgewicht	16800 kg
Leergewicht	4800 kg
Nutzlast	12000 kg
Fahrzeuglänge	9300 mm
Fahrzeugbreite	2550 mm
Fahrzeughöhe	3800 mm
Fahrzeugradstand	5100 mm

### AUFBAU

---

Aufbauhersteller	KRONE
Aufbaumodell	AZ 18F Koffer mit HB
Aufbauherstellungsjahr	2016
Aufbauinnenmasse l x b x h	7250 x 2500 x 2600 mm

### HEBEBÜHNE

---

Hebebühne	Hebebühne
Marke Hebebühne	DHOLLANDIA

# TRUCKTRADE

KEEP ON ROLLIN

Nutzlast Hebebühne	2000 Kg
Schildlänge Hebebühne	1800 mm
Hebebühne Jahrgang	2016

## GALLERY IMAGES



# TRUCKTRADE

KEEP ON ROLLIN



1) Spring and locked draw bar fitting, load distribution and retention

7) Restraint or additional locks

8) Functionality of the ABS/ES

9) Tires or lifts wheel clack engaged and secured

10) Parking brake released

**General maintenance:**

- 1) Check axles and chassis sets according to the manufacturer's instructions.
- 2) Grease bearing points and moving parts must be lubricated regularly
- 3) Brake shafts and brake cylinders must regularly be checked and readjusted. If necessary, make sure that the brake pad thickness meets the manufacturer's instructions.
- 4) Drain water from the air tank regularly
- 5) Position connector in decoupled condition into rest position
- 6) Parking the vehicle: Activate the parking brake and additionally secure with wheel chocks.

7) **ATTENTION!** Before all working repair work: Carefully cover all PVC lines, springs, or bellows etc.

8) Only use oil mineral cleaning agents. Minimum spraying distance for high-pressure or steam jet devices approx. 20 cm.

9) For new vehicles and in case of repairs after the first drive, regular oil change connections after 1000 km at the latest, and lockdowns, air lock systems as well as lockdowns, air lock systems are as authorized workshop and to have wear parts replaced in time.

949733 Werthe 30032268

**KRONE**

<b>KRONE</b>		Fahrzeugwerk Bernard Krone GmbH	
AZ		e1*2007/46*0942	
WKEAZ000000661426			
L:	9140 mm	kg	18000 kg
W:	2550 mm	1-	kg 1- 9000 kg T
Luft max:	9090 mm	2-	kg 2- 9000 kg T
b. max:	mm		

Manufacturer's loading plate (approved by CR 2011/100001)

# TRUCKTRADE

KEEP ON ROLLIN

